

## 1. IDENTIFICATION

**Product identifier**

**Product Name** WS Dark Mahogany

**Other means of identification**

**Product Code** 11816  
**SKU(s)** 11801, 11804, 11816

**Recommended use of the chemical and restrictions on use**

**Recommended Use** No information available.  
**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

<b>Supplier Address</b>	<b>Manufacturer Address</b>
Old Masters	
303 19th St. SE	
Orange City, IA 51041	
Phone: 712-737-4993	
Fax: 712-737-4997	

**Emergency telephone number**

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Flammable liquids	Category 3

**Emergency Overview**

<b>Danger</b>	
<b>Hazard statements</b>	May cause an allergic skin reaction May cause genetic defects May cause cancer Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Flammable liquid and vapor

**Appearance** No information available**Physical state** Liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Unknown acute toxicity 28.57 % of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%	Trade secret
Linseed Oil	8001-26-1	30 - 60	*
Mineral Spirits (Rule 66)	64742-47-8	10 - 30	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	1 - 5	*
Iron (III) oxide, as Fe	1309-37-1	1 - 5	*
Zirconium octoate	22464-99-9	1 - 5	*
Cobalt 2-ethylhexanoate	136-52-7	0.1 - 1	*
Crystalline Silica	14808-60-7	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Carbon Black	1333-86-4	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray (fog). Alcohol resistant foam.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

##### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Incompatible materials** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Iron (III) oxide, as Fe 1309-37-1	TWA: 5 mg/m <sup>3</sup> respirable particulate matter	TWA: 10 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> fume and total dust Iron oxide (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction regulated under Rouge	IDLH: 2500 mg/m <sup>3</sup> Fe dust and fume TWA: 5 mg/m <sup>3</sup> Fe dust and fume
Zirconium octoate 22464-99-9	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> Zr (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 10 mg/m <sup>3</sup> Zr	IDLH: 25 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr STEL: 10 mg/m <sup>3</sup> Zr
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

*NIOSH Immediately Dangerous to Life or Health*

**Other information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls**                      Showers  
 Eyewash stations  
 Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      Tight sealing safety goggles.

**Skin and body protection**                No special technical protective measures are necessary.

**Respiratory protection**                    If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**        When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point / freezing point</b>	No information available	
<b>Initial boiling point and boiling range</b>	No information available	
<b>Flash point</b>	39 °C / 102 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive limits</b>	No information available	
<b>Lower flammability or explosive limits</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Relative vapor density</b>	No information available	
<b>Specific gravity</b>	0.95	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>Liquid Density</b>	7.908 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	75.21%
<b>Percent volatile by weight</b>	24.79%

Percent solids by volume	70.2%
Actual VOC (lbs/gal)	2.0
Actual VOC (grams/liter)	235
EPA VOC (lbs/gal)	2.0
EPA VOC (grams/liter)	235
EPA VOC (lb/gal solids)	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

None known based on information supplied.

### Hazardous decomposition products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Linseed Oil 8001-26-1	> 15,000 mg/kg	-	-
Mineral Spirits (Rule 66) 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg ( Rat )	> 4000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Iron (III) oxide, as Fe 1309-37-1	> 10000 mg/kg ( Rat )	-	-
Zirconium octoate 22464-99-9	> 5000 mg/kg (Rat)	-	-
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg ( Rabbit )	> 10 mg/L ( Rat ) 1 h
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-
Mineral Spirits 64742-48-9	> 6000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4.83 mg/L ( Rat ) 4 h
Carbon Black	> 15400 mg/kg ( Rat )	-	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h

1333-86-4			
-----------	--	--	--

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Iron (III) oxide, as Fe 1309-37-1	-	Group 3	-	-
Cobalt 2-ethylhexanoate 136-52-7	-	Group 2B	Reasonably Anticipated	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Carbon Black 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A2 - Suspected Human Carcinogen  
 A3 - Animal Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Group 3 - Not classifiable as a human carcinogen  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Target organ effects** Eyes, Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Mineral Spirits (Rule 66) 64742-47-8	-	2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Iron (III) oxide, as Fe 1309-37-1	-	100000: 96 h Danio rerio mg/L LC50 static	-
Mineral Spirits 64742-48-9	-	2200: 96 h Pimephales promelas mg/L LC50	-
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Methyl Ethyl Ketoxime 96-29-7	0.65

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

**TDG** Not regulated

### 15. REGULATORY INFORMATION

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies \*

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Cobalt 2-ethylhexanoate - 136-52-7	0.1

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No



**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Crystalline Silica - 14808-60-7	Carcinogen
Carbon Black - 1333-86-4	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Toluene - 108-88-3	Developmental
Cumene - 98-82-8	Carcinogen
Ethylene Glycol - 107-21-1	Developmental
3,3'-Dichlorobenzidine - 91-94-1	Carcinogen

**U.S. State Right-to-Know Regulations**

This product does not contain any substances regulated by state right-to-know regulations

Chemical name	New Jersey	Massachusetts
Iron (III) oxide, as Fe 1309-37-1	X	X
Xylene 1330-20-7	X	X
Cobalt 2-ethylhexanoate 136-52-7	X	-
Crystalline Silica 14808-60-7	X	X
Carbon Black 1333-86-4	X	X

Chemical name	Pennsylvania
Linseed Oil 8001-26-1	X
Iron (III) oxide, as Fe 1309-37-1	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 2	<b>Instability</b> 0	<b>Special hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 2 *	<b>Flammability</b> 2	<b>Physical hazards</b> 0	<b>Personal protection</b> X

Chronic Hazard Star Legend      \* = *Chronic Health Hazard*

Revision date 24-Jul-2023

Revision Note  
No information available

**End of Safety Data Sheet**