



SAFETY DATA SHEET

Revision Date 26-Mar-2021

Version 2

1. IDENTIFICATION

Product identifier

Product Name MultiLac PreCat Lacquer Semi-Gloss

Other means of identification

Product Code 20-0124-05
UN/ID no UN1263
SKU(s) 20-0124-01, 20-0124-05

Recommended use of the chemical and restrictions on use

Recommended Use No information available.
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

Old Masters
303 19th St. SE
Orange City, IA 51041
Phone: 712-737-4993
Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause genetic defects
May cause cancer
May cause respiratory irritation. May cause drowsiness or dizziness
Highly flammable liquid and vapor

**Appearance** No information available**Physical state** Liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

- May be harmful if swallowed
- Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	30 - 60	*
Butyl Acetate	123-86-4	3 - 7	*
n-Butanol	71-36-3	3 - 7	*
Methyl Amyl Ketone	110-43-0	3 - 7	*
Nitrocellulose	9004-70-0	3 - 7	*
Solvent Naphtha, Light Aliphatic	64742-89-8	3 - 7	*
Isobutyl Alcohol	78-83-1	1 - 5	*
Isopropyl Alcohol	67-63-0	1 - 5	*

Hydrodesulfurized heavy pet. naphtha	64742-82-1	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Call a physician immediately.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. If breathing is difficult, give oxygen.
Ingestion	Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Extremely flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong acids. Strong oxidizing agents. Chlorinated compounds. Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Butyl Acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
n-Butanol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
Methyl Amyl Ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
Isobutyl Alcohol 78-83-1	TWA: 50 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 150 mg/m ³	IDLH: 1600 ppm TWA: 50 ppm TWA: 150 mg/m ³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

NIOSH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers Eyewash stations Ventilation systems.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Odor	No information available
Appearance	No information available	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	>= 56 °C / 133 °F	
Flash point	-17 °C / 1 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.89	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
Liquid Density	7.39 lbs/gal
Bulk density	No information available
Percent solids by weight	27.5%
Percent volatile by weight	32.4%
Percent solids by volume	19.9%
Actual VOC (lbs/gal)	2.4
Actual VOC (grams/liter)	287
EPA VOC (lbs/gal)	4.3

EPA VOC (grams/liter) 521.2
 EPA VOC (lb/gal solids) 12

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds. Acids.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Butyl Acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
n-Butanol 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit) = 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12.6 mL/kg (Rabbit) = 12600 µL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
Nitrocellulose 9004-70-0	> 5 g/kg (Rat)	-	-
Solvent Naphtha, Light Aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Isobutyl Alcohol 78-83-1	= 2460 mg/kg (Rat)	= 3400 mg/kg (Rabbit)	> 6.5 mg/L (Rat) 4 h
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Hydrodesulfurized heavy pet. naphtha 64742-82-1	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Nitrocellulose 9004-70-0	-	Group 2A	-	X
Isopropyl Alcohol 67-63-0	-	Group 3	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.

Target organ effects

Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

7.43% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Butyl Acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
n-Butanol 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1983: 48 h Daphnia magna mg/L EC50 1897 - 2072: 48 h Daphnia magna mg/L EC50 Static
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	-
Solvent Naphtha, Light Aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
Isobutyl Alcohol 78-83-1	230: 48 h Desmodesmus subspicatus mg/L EC50	375: 96 h Pimephales promelas mg/L LC50 static 1370 - 1670: 96 h	1070 - 1933: 48 h Daphnia magna mg/L EC50 Static 1300: 48 h

		Pimephales promelas mg/L LC50 flow-through 1480 - 1730: 96 h Lepomis macrochirus mg/L LC50 flow-through 1120 - 1520: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	Daphnia magna mg/L EC50
Isopropyl Alcohol 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
Hydrodesulfurized heavy pet. naphtha 64742-82-1	-	-	2.6: 96 h Chaetogammarus marinus mg/L LC50
Ethyl Benzene 100-41-4	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Butyl Acetate 123-86-4	1.81
n-Butanol 71-36-3	0.785
Methyl Amyl Ketone 110-43-0	1.98
Isobutyl Alcohol 78-83-1	0.79
Isopropyl Alcohol 67-63-0	0.05
Ethyl Benzene 100-41-4	3.2

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U001 U002 U019 U031 U045 U055 U108 U115 U122 U140 U147 U154 U220 U239

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
n-Butanol 71-36-3	-	Included in waste stream: F039	-	U031
Isobutyl Alcohol	U140	Included in waste streams:	-	U140

78-83-1		F005, F039		
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Butyl Acetate 123-86-4	Toxic
n-Butanol 71-36-3	Toxic
Nitrocellulose 9004-70-0	Ignitable in ether and alcohol Reactive in ether and alcohol
Isopropyl Alcohol 67-63-0	Toxic Ignitable
Ethyl Benzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Reportable Quantity (RQ) (Xylene: RQ (kg)= 45.40, Acetone: RQ (kg)= 2270.00)
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II
Emergency Response Guide Number 128

TDG

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions 59, 83
Description UN1263, Paint, 3, II

MEX

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Special Provisions 163
Packing Group II
Description UN1263, Paint, 3, II

ICAO (air)

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions A3, A72
Description UN1263, Paint, 3, II

IATA

UN Number UN1263
Proper shipping name Paint
Transport hazard class(es) 3

Packing Group	II
ERG Code	3L
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

IMDG

UN Number	UN1263
Transport hazard class(es)	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163
Description	UN1263, Paint, 3, II, (-17°C c.c.)

RID

UN/ID no	UN1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Labels	3

ADR

UN Number	UN1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II, (D/E)
Labels	3

ADN

Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01
Equipment Requirements	PP, EX, A

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
n-Butanol - 71-36-3	1.0
Isopropyl Alcohol - 67-63-0	1.0
Ethyl Benzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate 123-86-4	5000 lb	-	-	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butanol 71-36-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Isobutyl Alcohol 78-83-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Ethyl Benzene - 100-41-4	Carcinogen
Methanol - 67-56-1	Developmental
Formaldehyde - 50-00-0	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Methyl chloride (Chloromethane) - 74-87-3	Developmental Male Reproductive
Acetaldehyde - 75-07-0	Carcinogen
Ethylene oxide - 75-21-8	Carcinogen Developmental Female Reproductive Male Reproductive
Propylene oxide - 75-56-9	Carcinogen
1,4-Dioxane - 123-91-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Acetone	X	X

67-64-1		
Butyl Acetate 123-86-4	X	X
n-Butanol 71-36-3	X	X
Methyl Amyl Ketone 110-43-0	X	X
Nitrocellulose 9004-70-0	X	X
Isobutyl Alcohol 78-83-1	X	X
Isopropyl Alcohol 67-63-0	X	X
Xylene 1330-20-7	X	X
Ethyl Benzene 100-41-4	X	X

Chemical name	Pennsylvania
Acetone 67-64-1	X
Butyl Acetate 123-86-4	X
n-Butanol 71-36-3	X
Methyl Amyl Ketone 110-43-0	X
Nitrocellulose 9004-70-0	X
Isobutyl Alcohol 78-83-1	X
Isopropyl Alcohol 67-63-0	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Revision Date 26-Mar-2021

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet