

1. IDENTIFICATION

Product identifier

Product Name VersiVar Catalyst

Other means of identification

Product Code 26-0106-10
UN/ID no UN3469
SKU(s) 26-0106-02, 26-0106-10

Recommended use of the chemical and restrictions on use

Recommended Use No information available.
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address
 Old Masters
 303 19th St. SE
 Orange City, IA 51041
 Phone: 712-737-4993
 Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1 Sub-category C
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements

Causes severe skin burns and eye damage
 May cause cancer
 May cause respiratory irritation. May cause drowsiness or dizziness
 Highly flammable liquid and vapor



Appearance No information available**Physical state** Liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a POISON CENTER or doctor/physician
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Ethanol	64-17-5	30 - 60	*
Ethyl Acetate	141-78-6	10 - 30	*
Xylene Sulfonic Acid	25321-41-9	10 - 30	*
n-Propyl acetate	109-60-4	1 - 5	*
Isopropyl Alcohol	67-63-0	1 - 5	*
Sulfuric acid	7664-93-9	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****Eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.
 Consult a physician.

Skin Contact	Wash skin with soap and water.
Inhalation	If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents. Acids. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Ethyl Acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
n-Propyl acetate 109-60-4	STEL: 150 ppm TWA: 100 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Sulfuric acid 7664-93-9	TWA: 0.2 mg/m ³ thoracic particulate matter	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 15 mg/m ³ TWA: 1 mg/m ³

NIOSH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

No special technical protective measures are necessary.

Skin and body protection

No special technical protective measures are necessary.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Liquid

Appearance

No information available

Color

No information available

Odor

No information available

Odor threshold

No information available

Property

pH

Values

No information available

Melting point / freezing point

No information available

Remarks • Method

Boiling point / boiling range	>= 72 °C / 161 °F
Flash point	-4 °C / 25 °F
Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	0.89
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other Information

Softening point	No information available
Molecular weight	No information available
Liquid Density	7.41 lbs/gal
Bulk density	No information available
Percent solids by weight	17.7%
Percent volatile by weight	82.3%
Percent solids by volume	12.0%
Actual VOC (lbs/gal)	6.1
Actual VOC (grams/liter)	731.6
EPA VOC (lbs/gal)	6.1
EPA VOC (grams/liter)	731.6
EPA VOC (lb/gal solids)	50.8

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
----------------------------	-------------------

Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethanol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Ethyl Acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Xylene Sulfonic Acid 25321-41-9	= 7200 mg/kg (Rat)	-	-
n-Propyl acetate 109-60-4	= 8700 mg/kg (Rat)	> 17756 mg/kg (Rabbit)	-
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Sulfuric acid 7664-93-9	= 2140 mg/kg (Rat)	-	= 0.375 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X
Isopropyl Alcohol 67-63-0	-	Group 3	-	X
Sulfuric acid 7664-93-9	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic toxicity Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin.
Target organ effects blood, Central nervous system, Eyes, liver, Reproductive System, Respiratory system, Skin.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

17.27% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethanol 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	10800: 24 h Daphnia magna mg/L EC50 9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static
Ethyl Acetate 141-78-6	3300: 48 h Desmodesmus subspicatus mg/L EC50	220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	560: 48 h Daphnia magna mg/L EC50 Static
n-Propyl acetate 109-60-4	-	56 - 64: 96 h Pimephales promelas mg/L LC50 flow-through 56 - 64: 96 h Pimephales promelas mg/L LC50 static	318: 24 h Daphnia magna mg/L EC50
Isopropyl Alcohol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
Sulfuric acid 7664-93-9	-	500: 96 h Brachydanio rerio mg/L LC50 static	29: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Ethanol 64-17-5	-0.32
Ethyl Acetate 141-78-6	0.6
Isopropyl Alcohol 67-63-0	0.05

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U112 U239

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethyl Acetate 141-78-6	-	Included in waste stream: F039	-	U112

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Ethanol	Toxic

64-17-5	Ignitable
Ethyl Acetate 141-78-6	Toxic Ignitable
n-Propyl acetate 109-60-4	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable
Sulfuric acid 7664-93-9	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT

UN/ID no UN3469
Proper shipping name Paint related material, flammable, corrosive
Hazard class 3
Subsidiary class 8
Packing Group II
Reportable Quantity (RQ) (Ethyl Acetate: RQ (kg)= 2270.00)
Special Provisions IB2, T7, TP2, TP8, TP28
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II
Emergency Response Guide Number 132

TDG

UN/ID no UN3469
Proper shipping name Paint related material, flammable, corrosive
Hazard class 3
Subsidiary class 8
Packing Group II
Special Provisions 59
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II

MEX

UN/ID no UN3469
Proper shipping name Paint related material, flammable, corrosive
Hazard class 3
Subsidiary class 8
Special Provisions 163
Packing Group II
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II

ICAO (air)

UN/ID no UN3469
Proper shipping name Paint related material, flammable, corrosive
Hazard class 3
Subsidiary hazard class 8
Packing Group II
Special Provisions A3, A72
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II

IATA

UN Number UN3469
Proper shipping name Paint related material, flammable, corrosive
Transport hazard class(es) 3
Subsidiary hazard class 8
Packing Group II
ERG Code 3CH
Special Provisions A3, A72, A803
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II

IMDG

UN Number UN3469
Transport hazard class(es) 3
Subsidiary hazard class 8
Packing Group II
EmS-No F-E, S-C
Special Provisions 163
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II, (-4°C c.c.)

RID

UN/ID no UN3469
Proper shipping name Paint related material, flammable, corrosive
Transport hazard class(es) 3
Packing Group II
Classification code FC
Special Provisions 163
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II
Labels 8

ADR

UN Number UN3469
Proper shipping name Paint related material, flammable, corrosive
Transport hazard class(es) 3
Packing Group II
Classification code FC
Tunnel restriction code (D/E)
Special Provisions 163
Description UN3469, Paint related material, flammable, corrosive, 3 (8), II, (D/E)
Labels 3 + 8

ADN

Proper shipping name Paint related material, flammable, corrosive
Transport hazard class(es) 3
Packing Group II
Classification code FC
Special Provisions 163
Description UN3469, Paint related material, flammable, corrosive, 3 (+ 8), II
Hazard label(s) 3 + 8
Limited quantity (LQ) 1 L
Ventilation VE01
Equipment Requirements PP, EX, A

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Isopropyl Alcohol - 67-63-0	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes

Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sulfuric acid 7664-93-9	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethyl Acetate 141-78-6	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Sulfuric acid 7664-93-9	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental
Sulfuric acid - 7664-93-9	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Ethanol 64-17-5	X	X
Ethyl Acetate 141-78-6	X	X
n-Propyl acetate 109-60-4	X	X
Isopropyl Alcohol 67-63-0	X	X
Sulfuric acid 7664-93-9	X	X
Xylene 1330-20-7	X	X

Chemical name	Pennsylvania
Ethanol 64-17-5	X
Ethyl Acetate 141-78-6	X
n-Propyl acetate 109-60-4	X
Isopropyl Alcohol 67-63-0	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X

*Chronic Hazard Star Legend * = Chronic Health Hazard*

Revision Date 19-Oct-2021

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet