



# PROFESSIONAL



component, pre-catalyzed lacguer that provides excellent chemical and wear resistance.



## MultiLac

### Pre-Catalyzed Lacquer

For use on wood surfaces, kitchen cabinets, office and household furniture, and fine architectural woodwork including trim, windows, and doors. For wood substrates only. For interior use only.

#### **FEATURES**

- Superior performance to standard nitro-cellulose lacquers without having to add catalyst as is necessary with post-catalyzed lacquers or varnishes.
- Self-sealing technology
- HAPs compliant
- Meets KCMA and ASTM performance requirements when applied according to manufacturer's specifications



PHYSICAL PROPERTIES			
Solids Volume:	23%		
Solids Weight:	32%		
Theoretical Coverage:	374 sq. ft./gal		
Viscosity at 77°F:	20 to 25 seconds #2 Zahn		
Weight:	7.81 lb/gal		
Flash Point:	1°F		
Gloss at 60°:	Gloss Semi-Gloss Satin Dull Satin Flat	80+ 55 to 60 30 to 35 20 to 25 4 to 9	

<sup>\*</sup> For VOC information see Technical Data Sheet

#### MultiLac Pre-Catalyzed Lacquer Order Information

Sheen	Gallon	5 Gallon
Flat	20-0121-01	20-0121-05
Dull Satin	20-0122-01	20-0122-05
Satin	20-0123-01	20-0123-05
Semi-Gloss	20-0124-01	20-0124-05
Gloss	20-0125-01	20-0125-05

41039-OM (41039) 11/19



303 19th Street SE Orange City, Iowa 51041 (800) 747-3436 • myoldmasters.com/professional