

SAFETY DATA SHEET

Revision Date 16-Oct-2020 Version 7

1. IDENTIFICATION

Product identifier

Product Name Penetrating Stain Pecan

Other means of identification

Product Code 43904

SKU(s) 43901, 43904, 43916

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

Supplier Address

Old Masters 303 19th St. SE Orange City, IA 51041 Phone: 712-737-4993

Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin sensitization | Category 1 |
|---------------------|------------|
| Carcinogenicity | Category 2 |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 3 |

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction Suspected of causing cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



Appearance No information available

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- · May be harmful in contact with skin
- · Causes mild skin irritation
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Solvent Naphtha, Medium Aliphatic | 64742-88-7 | 30 - 60 | * |
| Linseed Oil | 8001-26-1 | 10 - 30 | * |
| 1,2,4-Trimethylbenzene | 95-63-6 | 1 - 5 | * |
| Xylene | 1330-20-7 | 1 - 5 | * |
| Ethyl Benzene | 100-41-4 | 0.1 - 1 | * |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1 - 1 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Call a physician immediately.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

Ingestion Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an

unconscious person. Get medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flammable. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up

with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH |
|-----------------------------------|-------------------------------|---|---|
| 1,2,4-Trimethylbenzene 95-63-6 | - | - | TWA: 25 ppm TWA: 125 mg/m ³ |
| Xylene 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³ | - 1 |
| Ethyl Benzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³ |

NIOSH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point Stapporation rate
No information available
No information available
No information available
No information available

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information available

Vapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.87

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

Liquid Density 7.29 lbs/gal

Bulk density No information available

Percent solids by weight 37.6% Percent volatile by weight 62.2% Percent solids by volume 30.2% Actual VOC (lbs/gal) 4.5 Actual VOC (grams/liter) 543.4 EPA VOC (lbs/gal) 4.5 EPA VOC (grams/liter) 544.2 EPA VOC (lb/gal solids) 15

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|--|--|
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | > 25 mL/kg (Rat) | > 3000 mg/kg (Rabbit) | > 13 mg/L (Rat)4 h |
| Linseed Oil 8001-26-1 | > 15,000 mg/kg | - | - |
| 1,2,4-Trimethylbenzene 95-63-6 | = 3280 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 18 g/m³ (Rat) 4 h |
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h |
| Ethyl Benzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat)4 h |
| Methyl Ethyl Ketoxime 96-29-7 | = 930 mg/kg (Rat) | 1000 - 1800 mg/kg (Rabbit) | > 4.83 mg/L (Rat)4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|----------|-----|------|
| Xylene | - | Group 3 | - | - |
| 1330-20-7 | | • | | |
| Ethyl Benzene | A3 | Group 2B | - | X |
| 100-41-4 | | • | | |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated

overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory

system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone

marrow and blood-forming system.

Target organ effects blood, Central nervous system, Eyes, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

4.56% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|-----------------------------------|-------------------------------|---------------------------------|---------------------------------|
| Solvent Naphtha, Medium Aliphatic | 450: 96 h Pseudokirchneriella | 800: 96 h Pimephales promelas | 100: 48 h Daphnia magna mg/L |
| 64742-88-7 | subcapitata mg/L EC50 | mg/L LC50 static | EC50 |
| 1,2,4-Trimethylbenzene | ,2,4-Trimethylbenzene - | | 6.14: 48 h Daphnia magna mg/L |
| 95-63-6 | | promelas mg/L LC50 flow-through | EC50 |
| Xylene | - | 13.4: 96 h Pimephales promelas | 3.82: 48 h water flea mg/L EC50 |

| 1330-20-7 | | mg/L LC50 flow-through 13.1 - 16.5: | 0.6: 48 h Gammarus lacustris mg/l |
|-----------------------|-------------------------------------|-------------------------------------|------------------------------------|
| 1000 20 7 | | 96 h Lepomis macrochirus mg/L | LC50 |
| | | LC50 flow-through 13.5 - 17.3: 96 h | |
| | | Oncorhynchus mykiss mg/L LC50 | |
| | | 30.26 - 40.75: 96 h Poecilia | |
| | | reticulata mg/L LC50 static 2.661 - | |
| | | 4.093: 96 h Oncorhynchus mykiss | |
| | | mg/L LC50 static 23.53 - 29.97: 96 | |
| | | h Pimephales promelas mg/L LC50 | |
| | | static 780: 96 h Cyprinus carpio | |
| | | mg/L LC50 semi-static 780: 96 h | |
| | | Cyprinus carpio mg/L LC50 7.711 - | |
| | | 9.591: 96 h Lepomis macrochirus | |
| | | mg/L LC50 static 19: 96 h Lepomis | |
| | | macrochirus mg/L LC50 | |
| Ethyl Benzene | 438: 96 h Pseudokirchneriella | 11.0 - 18.0: 96 h Oncorhynchus | 1.8 - 2.4: 48 h Daphnia magna mg/L |
| 100-41-4 | subcapitata mg/L EC50 2.6 - 11.3: | mykiss mg/L LC50 static 4.2: 96 h | EC50 |
| | 72 h Pseudokirchneriella | Oncorhynchus mykiss mg/L LC50 | |
| | subcapitata mg/L EC50 static 4.6: | semi-static 7.55 - 11: 96 h | |
| | 72 h Pseudokirchneriella | Pimephales promelas mg/L LC50 | |
| | subcapitata mg/L EC50 1.7 - 7.6: 96 | | |
| | h Pseudokirchneriella subcapitata | Pimephales promelas mg/L LC50 | |
| | mg/L EC50 static | static 32: 96 h Lepomis macrochirus | |
| | | mg/L LC50 static 9.6: 96 h Poecilia | |
| | | reticulata mg/L LC50 static | |
| Methyl Ethyl Ketoxime | 83: 72 h Desmodesmus subspicatus | j i | 750: 48 h Daphnia magna mg/L |
| 96-29-7 | mg/L EC50 | LC50 static 320 - 1000: 96 h | EC50 |
| | | Leuciscus idus mg/L LC50 static | |
| | | 777 - 914: 96 h Pimephales | |
| | | promelas mg/L LC50 flow-through | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|-----------------------------------|-----------------------|
| 1,2,4-Trimethylbenzene 95-63-6 | 3.63 |
| Xylene 1330-20-7 | 2.77 - 3.15 |
| Ethyl Benzene 100-41-4 | 3.2 |
| Methyl Ethyl Ketoxime 96-29-7 | 0.65 |

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U019 U055 U220 U239

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------|------|---------------------------|------------------------|------------------------|
| Xylene | - | Included in waste stream: | - | U239 |
| 1330-20-7 | | F039 | | |
| Ethyl Benzene | - | Included in waste stream: | - | - |
| 100-41-4 | | F039 | | |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | California Hazardous Waste Status |
|---------------|-----------------------------------|
| Xylene | Toxic |
| 1330-20-7 | Ignitable |
| Ethyl Benzene | Toxic |
| 100-41-4 | Ignitable |

14. TRANSPORT INFORMATION

Not regulated DOT Not regulated **TDG**

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies *

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | SARA 313 - Threshold Values % |
|----------------------------------|-------------------------------|
| 1,2,4-Trimethylbenzene - 95-63-6 | 1.0 |
| Xylene - 1330-20-7 | 1.0 |
| Ethyl Benzene - 100-41-4 | 0.1 |

SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** No Fire hazard Yes Sudden release of pressure hazard No **Reactive Hazard** No

<u>CWA (Clean Water Act)</u>
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene 1330-20-7 | 100 lb | - | - | X |
| Ethyl Benzene 100-41-4 | 1000 lb | X | X | X |

CERCLA

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Xylene | 100 lb | - | RQ 100 lb final RQ |
| 1330-20-7 | | | RQ 45.4 kg final RQ |
| Ethyl Benzene | 1000 lb | - | RQ 1000 lb final RQ |
| 100-41-4 | | | RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical name | California Proposition 65 | |
|--|---------------------------|--|
| Ethyl Benzene - 100-41-4 | Carcinogen | |
| Carbon Black - 1333-86-4 | Carcinogen | |
| Crystalline Silica - 14808-60-7 | Carcinogen | |
| Benzene(including benzene from gasoline) - 71-43-2 | Carcinogen | |
| | Developmental | |
| | Male Reproductive | |
| Cumene - 98-82-8 | Carcinogen | |
| Toluene - 108-88-3 | Developmental | |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts |
|------------------------|------------|---------------|
| 1,2,4-Trimethylbenzene | X | X |
| 95-63-6 | | |
| Xylene | X | X |
| 1330-20-7 | | |
| Ethyl Benzene | X | X |
| 100-41-4 | | |

| Chemical name | Pennsylvania |
|------------------------|--------------|
| Linseed Oil | X |
| 8001-26-1 | |
| 1,2,4-Trimethylbenzene | X |
| 95-63-6 | |
| Xylene | X |
| 1330-20-7 | |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

| Chemical name | Weight % of HAPS in Product | Pounds HAPS / Gal Product |
|---------------|-----------------------------|---------------------------|
| Xylene | 1.80% | 0.13 |
| 1330-20-7 | | |

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and chemical

properties -

HMIS Health hazards 2 * Flammability 2 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 16-Oct-2020

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage,

transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet