

FAST DRY STAIN

INTERIOR • OIL BASED • PENETRATING



High Quality Interior Penetrating Stain
Designed for the
Master Craftsperson

- Applies easily with rapid 30 minute dry time
- Ability to topcoat quickly, granting a more efficient turnaround
- Deep color intensity and clarity
- Preferred for hardwoods, such as oak, ash, walnut, and mahogany
- 24 ready-mix colors



Ola Masters
CRAFTSMAN QUALITY FINISHES

Old Masters®

Speed • Versatility • Performance

Old Masters Fast Dry Stain is a high quality, interior oil-based stain that applies easily and enhances the wood's natural grain with its intensified depth of color and clarity. Its rapid dry time and superior performance allow every project to be topcoated more quickly, granting a more efficient turnaround. The stain may be brushed, sprayed, or wiped onto the surface. Makes a great alternative to lacquer stains. Experience optimal results on all interior wood surfaces such as cabinets, doors, floors, furniture, and woodwork.

Topcoat: This stain is compatible with all clear finishes including professional finishes such as lacquers and conversion finishes. Wait 24 hours before topcoating with a water-based clear finish.

Stain Color: Choose from one of 24 ready-mix colors, achieve your desired color by intermixing with other colors, or tint with universal or industrial colorant to create custom stain colors.

DANGER: Rags, steel wool, sanding residue, and other wastes used or soaked with this product may spontaneously catch fire if improperly discarded. No ignition source is required for these wastes to start on fire by themselves. Immediately place rags, steel wool, sanding residue, and other wastes used or soaked with this product in a sealed, water-filled metal container. Dispose of in accordance with local fire regulations.



Rich Tone stains contain extra pigment, creating deep color intensity. Colors shown are produced as close as modern printing techniques permit and are only approximate representations of the actual colors.

Fast Dry Product Information	
Solids By Volume	29.4% to 29.6%
Solids By Weight	35.7% to 44.9%
Weight per Gallon	7.1 to 8.3 lbs
Recommended Dry Film Thickness per Coat	N/A
Coverage at Recommended Dry Film Thickness	N/A
Flash Point	102°F Tag Closed Cup
Viscosity at 77°	25 to 27 secs. #2 Ford Cup
Dry Time to Touch	30 to 60 minutes at 70°F and 50% Relative Humidity
Vehicle	Alkyd
VOCs	See Technical Data Sheet

49975-OM (68372) 05/23



303 19th Street SE • PO Box 286 • Orange City, IA 51041
 (800) 747-3436 • info@myoldmasters.com
 myoldmasters.com