

SAFETY DATA SHEET

Revision Date 30-Jul-2021

Version 9

1. IDENTIFICATION

Product identifier Product Name

Gel Stain Fruitwood

 Other means of identification
 80904

 Product Code
 80901, 80904, 80908, 80916

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet Supplier Address Old Masters 303 19th St. SE Orange City, IA 51041 Phone: 712-737-4993 Fax: 712-737-4997

Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin sensitization | Category 1 |
|------------------------|-------------|
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 3 |

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



I.

Т

| Appearance No information available | Physical state Liquid | Odor No information available |
|-------------------------------------|-----------------------|-------------------------------|

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- May be harmful in contact with skin
- Causes mild skin irritation
- Harmful to aquatic life with long lasting effects
- Harmful to aquatic life
- Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Solvent Naphtha, Medium Aliphatic | 64742-88-7 | 30 - 60 | * |
| Mineral Spirits (Rule 66) | 64742-47-8 | 7 - 13 | * |
| Titanium dioxide | 13463-67-7 | 3 - 7 | * |
| Xylene | 1330-20-7 | 1 - 5 | * |
| 1,2,4-Trimethylbenzene | 95-63-6 | 1 - 5 | * |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1 - 1 | * |
| Ethyl Benzene | 100-41-4 | 0.1 - 1 | * |
| Mineral Spirits | 64742-48-9 | 0.1 - 1 | * |
| Crystalline Silica | 14808-60-7 | 0.1 - 1 | * |
| Cobalt 2-ethylhexanoate | 136-52-7 | 0.1 - 1 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| Eye contact | Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician. | | |
|--|--|--|--|
| Skin Contact | Call a physician immediately. | | |
| Inhalation | Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. | | |
| Ingestion | Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to ar unconscious person. Get medical attention. | | |
| Most important symptoms and effects, both acute and delayed | | | |
| Symptoms | No information available. | | |
| Indication of any immediate medical attention and special treatment needed | | | |
| Note to physicians | Treat symptomatically. | | |
| 5. FIRE-FIGHTING MEASURES | | | |

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| Personal precautions | Remove all sources of ignition. Use personal protective equipment as required. | | |
|--|---|--|--|
| Environmental precautions | | | |
| Environmental precautions | Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. | | |
| Methods and material for containment and cleaning up | | | |
| Methods for containment | Prevent further leakage or spillage if safe to do so. | | |
| Methods for cleaning up | Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material. | | |
| 7. HANDLING AND STORAGE | | | |
| Precautions for safe handling | | | |

Advice on safe handling Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH |
|------------------------|---|--|--|
| Titanium dioxide | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| 13463-67-7 | | TWA: 5 mg/m ³ respirable fraction | TWA: 2.4 mg/m ³ CIB 63 fine |
| | | | TWA: 0.3 mg/m ³ CIB 63 ultrafine, |
| | | | including engineered nanoscale |
| Xylene | STEL: 150 ppm | TWA: 100 ppm | - |
| 1330-20-7 | TWA: 100 ppm | TWA: 435 mg/m ³ | |
| | | (vacated) TWA: 100 ppm | |
| | | (vacated) TWA: 435 mg/m ³ | |
| | | (vacated) STEL: 150 ppm | |
| | | (vacated) STEL: 655 mg/m ³ | |
| 1,2,4-Trimethylbenzene | - | - | TWA: 25 ppm |
| 95-63-6 | | | TWA: 125 mg/m ³ |
| Ethyl Benzene | TWA: 20 ppm | TWA: 100 ppm | IDLH: 800 ppm |
| 100-41-4 | | TWA: 435 mg/m ³ | TWA: 100 ppm |
| | | (vacated) TWA: 100 ppm | TWA: 435 mg/m ³ |
| | | (vacated) TWA: 435 mg/m ³ | STEL: 125 ppm |
| | | (vacated) STEL: 125 ppm | STEL: 545 mg/m ³ |
| | | (vacated) STEL: 545 mg/m ³ | |
| Crystalline Silica | TWA: 0.025 mg/m ³ respirable | TWA: 50 μg/m³ TWA: 50 μg/m³ | IDLH: 50 mg/m ³ respirable dust |
| 14808-60-7 | particulate matter | excludes construction work, | TWA: 0.05 mg/m ³ respirable dust |
| | | agricultural operations, and | |
| | | exposures that result from the | |
| | | processing of sorptive clays | |
| | | (vacated) TWA: 0.1 mg/m ³ | |
| | | respirable dust | |
| | | : (250)/(%SiO2 + 5) mppcf TWA | |
| | | respirable fraction | |
| | | : (10)/(%SiO2 + 2) mg/m ³ TWA | |
| | | respirable fraction | |

NIOSH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

| Engineering Controls | Showers |
|----------------------|----------------------|
| | Eyewash stations |
| | Ventilation systems. |

Individual protection measures, such as personal protective equipment

| Eye/face protection | No special technical protective measures are necessary. |
|--------------------------------|---|
| Skin and body protection | No special technical protective measures are necessary. |
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Physical state Appearance Color | Liquid No information available No information available | Odor Odor threshold | No information available No information available |
|--|---|-------------------------|--|
| Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties | ValuesNo information availableNo information available>= $80 ^{\circ}C / 176 ^{\circ}F$ $39 ^{\circ}C / 102 ^{\circ}F$ No information availableNo information available | <u>Remarks • Method</u> | |
| Other Information | | | |
| Softening point Molecular weight Liquid Density Bulk density Percent solids by weight Percent volatile by weight Percent solids by volume Actual VOC (lbs/gal) Actual VOC (grams/liter) EPA VOC (lbs/gal) EPA VOC (grams/liter) EPA VOC (lb/gal solids) | No information available No information available 7.83 lbs/gal No information available 41.7% 58.3% 30.1% 4.6 547 4.6 547 15.2 | | |

10. STABILITY AND REACTIVITY

Reactivity No data available

No data avallable

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Product Information | No data available |
|---------------------|--------------------|
| Inhalation | No data available. |
| Eye contact | No data available. |
| Skin Contact | No data available. |
| Ingestion | No data available. |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|----------------------|---|--|
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | > 25 mL/kg (Rat) | > 3000 mg/kg (Rabbit) | > 13 mg/L (Rat)4 h |
| Mineral Spirits (Rule 66) 64742-47-8 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat)4 h |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 1700 mg/kg (Rabbit)> 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h |
| ,2,4-Trimethylbenzene = 3280 mg/kg (Rat) 95-63-6 | | > 3160 mg/kg (Rabbit) | = 18 g/m³(Rat)4 h |
| Vlethyl Ethyl Ketoxime = 930 mg/kg (Rat) 96-29-7 | | 1000 - 1800 mg/kg (Rabbit) | > 4.83 mg/L (Rat)4 h |
| Ethyl Benzene = 3500 mg/kg (Rat) 100-41-4 | | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat)4 h |
| Mineral Spirits > 6000 mg/kg (Rat) 64742-48-9 | | > 3160 mg/kg (Rabbit) | > 8500 mg/m³(Rat)4 h |
| Crystalline Silica 14808-60-7 | > 22,500 mg/kg (Rat) | - | - |
| Cobalt 2-ethylhexanoate 136-52-7 | = 1300 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | > 10 mg/L (Rat)1 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Sensitization Germ cell mutagenicity Carcinogenicity | No informati | on available. on available. on available. | | |
|--|--------------|---|------------------------|------|
| Chemical name | ACGIH | IARC | NTP | OSHA |
| Titanium dioxide 13463-67-7 | - | Group 2B | - | Х |
| Xylene 1330-20-7 | - | Group 3 | - | - |
| Ethyl Benzene 100-41-4 | A3 | Group 2B | - | Х |
| Crystalline Silica 14808-60-7 | A2 | Group 1 | Known | Х |
| Cobalt 2-ethylhexanoate 136-52-7 | - | Group 2B | Reasonably Anticipated | Х |

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

| A3 - Animal Carcinogen | |
|---|--|
| IARC (International Agency for Rese | arch on Cancer) |
| Group 1 - Carcinogenic to Humans | |
| Group 2B - Possibly Carcinogenic to H | umans |
| Group 3 - Not classifiable as a human of | carcinogen |
| NTP (National Toxicology Program) | |
| Known - Known Carcinogen | |
| Reasonably Anticipated - Reasonably | Anticipated to be a Human Carcinogen |
| OSHA (Occupational Safety and Hea | Ith Administration of the US Department of Labor) |
| X - Present | |
| Reproductive toxicity | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Chronic toxicity | Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone marrow and blood-forming system. |
| Target organ effects Aspiration hazard | blood, Central nervous system, Eyes, Lungs, Respiratory system, Skin. No information available. |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|---|---|---|--|
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | 450: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 800: 96 h Pimephales promelas mg/L LC50 static | 100: 48 h Daphnia magna mg/L EC50 |
| Mineral Spirits (Rule 66) 64742-47-8 | - | 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static | 4720: 96 h Den-dronereides heteropoda mg/L LC50 |
| Xylene 1330-20-7 | - | 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 19: 96 h Lepomis macrochirus mg/L LC50 | LC50 |
| 1,2,4-Trimethylbenzene 95-63-6 | - | 7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through | 6.14: 48 h Daphnia magna mg/L EC50 |
| Methyl Ethyl Ketoxime 96-29-7 | 83: 72 h Desmodesmus subspicatus mg/L EC50 | 760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through | 750: 48 h Daphnia magna mg/L EC50 |
| Ethyl Benzene 100-41-4 | 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: | 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h | 1.8 - 2.4: 48 h Daphnia magna mg/L EC50 |

| | 5 | Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static | |
|-----------------|---|--|----------------------------------|
| Mineral Spirits | - | 0 | 2.6: 96 h Chaetogammarus marinus |
| 64742-48-9 | | mg/L LC50 | mg/L LC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|-----------------------------------|-----------------------|
| Xylene 1330-20-7 | 2.77 - 3.15 |
| 1,2,4-Trimethylbenzene 95-63-6 | 3.63 |
| Methyl Ethyl Ketoxime 96-29-7 | 0.65 |
| Ethyl Benzene 100-41-4 | 3.2 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number

D001 U019 U055 U220 U239

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------|------|---------------------------|------------------------|------------------------|
| Xylene | - | Included in waste stream: | - | U239 |
| 1330-20-7 | | F039 | | |
| Ethyl Benzene | - | Included in waste stream: | - | - |
| 100-41-4 | | F039 | | |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | California Hazardous Waste Status |
|-------------------------|-----------------------------------|
| Xylene | Toxic |
| 1330-20-7 | Ignitable |
| Ethyl Benzene | Toxic |
| 100-41-4 | Ignitable |
| Cobalt 2-ethylhexanoate | Toxic |
| 136-52-7 | |

14. TRANSPORT INFORMATION

DOT Not regulated

TDG

Not regulated

15. REGULATORY INFORMATION

| International Inventories | |
|---------------------------|------------|
| TSCA | Complies |
| DSL/NDSL | Complies * |

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | SARA 313 - Threshold Values % |
|----------------------------------|-------------------------------|
| Xylene - 1330-20-7 | 1.0 |
| 1,2,4-Trimethylbenzene - 95-63-6 | 1.0 |
| Ethyl Benzene - 100-41-4 | 0.1 |

SARA 311/312 Hazard Categories

| Acute health hazard | Yes |
|-----------------------------------|-----|
| Chronic Health Hazard | No |
| Fire hazard | Yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene 1330-20-7 | 100 lb | - | - | Х |
| Ethyl Benzene 100-41-4 | 1000 lb | X | X | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Xylene | 100 lb | - | RQ 100 lb final RQ |
| 1330-20-7 | | | RQ 45.4 kg final RQ |
| Ethyl Benzene | 1000 lb | - | RQ 1000 lb final RQ |
| 100-41-4 | | | RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical name | California Proposition 65 |
|---------------------------------|---------------------------|
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Ethyl Benzene - 100-41-4 | Carcinogen |
| Crystalline Silica - 14808-60-7 | Carcinogen |
| Carbon Black - 1333-86-4 | Carcinogen |

| Toluene - 108-88-3 | Developmental |
|--|-------------------|
| Benzene(including benzene from gasoline) - 71-43-2 | Carcinogen |
| | Developmental |
| | Male Reproductive |
| Cumene - 98-82-8 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts |
|-------------------------------------|------------|---------------|
| Titanium dioxide 13463-67-7 | Х | X |
| Xylene 1330-20-7 | Х | Х |
| 1,2,4-Trimethylbenzene 95-63-6 | Х | X |
| Ethyl Benzene 100-41-4 | Х | X |
| Crystalline Silica 14808-60-7 | Х | X |
| Cobalt 2-ethylhexanoate 136-52-7 | Х | - |

| Chemical name | Pennsylvania |
|------------------------|--------------|
| Titanium dioxide | Х |
| 13463-67-7 | |
| Xylene | Х |
| 1330-20-7 | |
| 1,2,4-Trimethylbenzene | Х |
| 95-63-6 | |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

| Chemical name | Weight % of HAPS in Product | Pounds HAPS / Gal Product |
|---------------|-----------------------------|---------------------------|
| Xylene | 1.87% | 0.15 |
| 1330-20-7 | | |

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| <u>NFPA</u> | Health hazards 2 | Flammability 2 | Instability 0 | Physical and chemical |
|------------------------|--------------------|-----------------|--------------------|-----------------------|
| | | | | properties - |
| HMIS | Health hazards 2 * | Flammability 2 | Physical hazards 0 | Personal protection X |
| Chronic Hazard Star Le | eaend * = Chroni | c Health Hazard | | |

Revision Date

30-Jul-2021

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet