

SAFETY DATA SHEET

Revision Date 12-Jul-2021

Version 9

1. IDENTIFICATION

Product identifier Product Name

Gel Stain Maple

 Other means of identification
 81208

 Product Code
 81201, 81204, 81208, 81216

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet Supplier Address Old Masters 303 19th St. SE Orange City, IA 51041 Phone: 712-737-4993 Fax: 712-737-4997

Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



L

Appearance No information available	Physical state Liquid	Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- May be harmful in contact with skin
- Causes mild skin irritation
- Harmful to aquatic life with long lasting effects
- Harmful to aquatic life
- Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Solvent Naphtha, Medium Aliphatic	64742-88-7	30 - 60	*
Mineral Spirits (Rule 66)	64742-47-8	10 - 30	*
Xylene	1330-20-7	1 - 5	*
1,2,4-Trimethylbenzene	95-63-6	1 - 5	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin Contact	Call a physician immediately.	
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.	
Ingestion	Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.	
Most important symptoms and effects, both acute and delayed		
Symptoms	No information available.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures		
Personal precautions	Remove all sources of ignition. Use personal protective equipment as required.	
Environmental precautions		
Environmental precautions	Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.	
Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.		
7. HANDLING AND STORAGE		

7. HANDLING AND STORAGE		
Precautions for safe handling		
Advice on safe handling	Avoid contact with skin, eyes or clothing.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric	

motors and static electricity).

Incompatible materials

Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
1,2,4-Trimethylbenzene	-	-	TWA: 25 ppm
95-63-6			TWA: 125 mg/m ³
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	-

NIOSH Immediately Dangerous to Life or Health

```
Other Information
```

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment

.

Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Liquid No information available No information available	Odor Odor threshold	No information available No information available
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	<u>Values</u> No information available No information available >= 80 °C / 176 °F 39 °C / 102 °F No information available No information available	<u>Remarks • Method</u>	

Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient	No information available No information available No information available No information available 0.94 No information available No information available No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Other Information	
Softening point	No information available
Molecular weight	No information available
Liquid Density	7.80 lbs/gal
Bulk density	No information available
Percent solids by weight	41.4%
Percent volatile by weight	58.6%
Percent solids by volume	30.0%
Actual VOC (lbs/gal)	4.6
Actual VOC (grams/liter)	547.5 4.6
EPA VOC (Ibs/gal)	4.0 547.5
EPA VOC (grams/liter)	547.5 15.2
EPA VOC (lb/gal solids)	10.2

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.

Ingestion No data available.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat)4 h
Mineral Spirits (Rule 66) 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit)> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat)4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m³ (Rat)4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No informatio	on available.		
Germ cell mutagenicity	No information available.			
Carcinogenicity	No information	on available.		
Chemical name	ACGIH	IARC	NTP	OSHA
Xylene	-	Group 3	-	-
1330-20-7				
Ethyl Benzene	A3	Group 2B	-	X
100-41-4				
	erence of Governmental Inc	lustrial Hygienists)		
A3 - Animal Carcinogen				
	ency for Research on Cance	er)		
Group 2B - Possibly Card				
Group 3 - Not classifiable				
	afety and Health Administra	tion of the US Department o	of Labor)	
	X - Present			
Reproductive toxicity	No information			
STOT - single exposure	No information available.			
STOT - repeated exposu	Ire No information available.			
Chronic toxicity	Ethylbenzene has been classified by the International Agency for Research on Cancer			
-	(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated			
	overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory			
	system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone			
	marrow and blood-forming system.			
Target ergen effecte		al nervous system, Eyes, R	Coopiratory system Skin	
Target organ effects			Cespiratory system, SKIN.	
Aspiration hazard	No information	n avallable.		

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

9.96% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea	

Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Mineral Spirits (Rule 66)		45: 96 h Pimephales promelas mg/L	
64742-47-8		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
0		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
Xylene	-	13.4: 96 h Pimephales promelas	3.82: 48 h water flea mg/L EC50
1330-20-7		mg/L LC50 flow-through 13.1 - 16.5:	0.6: 48 h Gammarus lacustris mg/l
		96 h Lepomis macrochirus mg/L	LC50
		LC50 flow-through 13.5 - 17.3: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		30.26 - 40.75: 96 h Poecilia	
		reticulata mg/L LC50 static 2.661 -	
		4.093: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 23.53 - 29.97: 96	
		h Pimephales promelas mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 780: 96 h	
		Cyprinus carpio mg/L LC50 7.711 -	
		9.591: 96 h Lepomis macrochirus	
		mg/L LC50 static 19: 96 h Lepomis	
		macrochirus mg/L LC50	
1,2,4-Trimethylbenzene	-	7.19 - 8.28: 96 h Pimephales	6.14: 48 h Daphnia magna mg/L
95-63-6		promelas mg/L LC50 flow-through	EC50
Methyl Ethyl Ketoxime	83: 72 h Desmodesmus subspicatus	0	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	LC50 static 320 - 1000: 96 h	EC50
		Leuciscus idus mg/L LC50 static	
		777 - 914: 96 h Pimephales	
		promelas mg/L LC50 flow-through	
Ethyl Benzene	438: 96 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/
100-41-4	subcapitata mg/L EC50 2.6 - 11.3:	mykiss mg/L LC50 static 4.2: 96 h	EC50
	72 h Pseudokirchneriella	Oncorhynchus mykiss mg/L LC50	
	subcapitata mg/L EC50 static 4.6:	semi-static 7.55 - 11: 96 h	
	72 h Pseudokirchneriella	Pimephales promelas mg/L LC50	
	subcapitata mg/L EC50 1.7 - 7.6: 96		
	h Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	
	mg/L EC50 static	static 32: 96 h Lepomis macrochirus	
		mg/L LC50 static 9.6: 96 h Poecilia	
Missingh Optimite		reticulata mg/L LC50 static	
Mineral Spirits	-		2.6: 96 h Chaetogammarus marinu
64742-48-9		mg/L LC50	mg/L LC50

Persistence and degradability No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
1,2,4-Trimethylbenzene 95-63-6	3.63
Methyl Ethyl Ketoxime 96-29-7	0.65
Ethyl Benzene 100-41-4	3.2

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U019 U055 U220 U239

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene	-	Included in waste stream:	-	U239
1330-20-7		F039		
Ethyl Benzene	-	Included in waste stream:	-	-
100-41-4		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethyl Benzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

DOT	Not regulated
TDG	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
1,2,4-Trimethylbenzene - 95-63-6	1.0
Ethyl Benzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethyl Benzene 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethyl Benzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65	
Ethyl Benzene - 100-41-4	Carcinogen	
Crystalline Silica - 14808-60-7	Carcinogen	
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen	
	Developmental	
	Male Reproductive	
Cumene - 98-82-8	Carcinogen	
Toluene - 108-88-3	Developmental	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Xylene 1330-20-7	Х	Х
1,2,4-Trimethylbenzene 95-63-6	Х	Х
Ethyl Benzene 100-41-4	Х	Х

Chemical name	Pennsylvania
Xylene	Х
1330-20-7	
1,2,4-Trimethylbenzene	X
95-63-6	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene	1.84%	0.14
1330-20-7		

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and chemical properties -
<u>HMIS</u> Chronic Hazard Star Le	Health hazards 2 * egend *= Chroni	Flammability 2 c Health Hazard	Physical hazards 0	Personal protection X

Revision Date

12-Jul-2021

Revision Note No information available Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet