



# Technical Data Sheet

## PASTE WAX

### Description

Old Masters Paste Wax is formulated with imported Carnauba, the hardest natural wax known to man. It provides outstanding durability while enhancing the beauty of furniture and woodwork. This product does not contain beeswax or silicone.

### Directions For Use

All surfaces must be clean, dry and free from dirt, wax, grease, glue and other contaminants. Apply wax evenly with a clean, lint-free cloth. A thin coating produces the best results. Allow wax to dry thoroughly before polishing. On new surfaces, a second application is recommended. Not recommended for asphalt tile.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Helpful Hints

Thin coats dry faster and harder than thick ones. It is important that each coat be completely dry before applying the next one. If a soft layer is trapped beneath the top one, it will never harden.

Keep away from heat, sparks and open flame. Use adequate ventilation. Avoid prolonged or repeated contact with skin.

### Limited Warranty

Since Old Masters does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters liability will under no circumstances exceed the replacement of the product.

### Product Codes

30901 Pint

### Technical Data

#### Product Information

Solids by Volume	20%
Solids by Weight	20%
Weight per Gallon	6.4 lbs
Vehicle	Wax
Viscosity at 77°F	Gel
Flash Point	102°F Tag Closed Cup
Recommended Thinner	Do not thin. Used as packaged.
VOCs	80% (estimated)

#### Coverage

Theoretical Coverage @ Mil DFT	1600 sq ft/gal
Coverage @ Recommended DFT	N/A
Recommended DFT Per Coat	N/A

#### Dry Time

At 70°F and 50% Relative Humidity	15 to 30 minutes
-----------------------------------	------------------

REVISED 08/2025