

MASTERS ARMOR® PART B HARDENER

Description

Masters Armor Part B Hardener is an additive for Masters Armor Water-Based Clear Finish. The Hardener Additive provides maximum protection and durability for high traffic floor areas, bar and table tops. For use with Masters Armor Interior Water-Based Clear Finish only.

Directions for Use

1. Add 4 ounces per gallon.
2. Mix in slowly.
3. Stir thoroughly.

Pot life is 72 hours once added to Masters Armor Water-Based Clear Finish.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MAX VOC

MAXIMUM VOC DOES NOT EXCEED 107 g/L when mixed with Part A.

Limited Warranty

Since Old Masters does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters liability will under no circumstances exceed the replacement of the product.

Product Codes

72432 4 Ounces

Technical Data

Product Information

Solids by Volume	41.2%
Solids by Weight	41.3%
Weight per Gallon	8.3 lbs
Vehicle	Water
Viscosity at 77°F	19.65 secs. #2 Zahn
Flash Point	>= 102°F Tag Closed Cup
Recommended Thinner	Do not thin. Used as packaged.
VOCs	<25 g/L

Coverage

Theoretical Coverage @Mil DFT	N/A
Coverage @ Recommended DFT	N/A
Recommended DFT Per Coat	N/A

Dry Time

At 70°F and 50% Relative Humidity	N/A
-----------------------------------	-----