

## TUNG OIL

### Description

Old Masters Tung Oil creates a beautiful, hand rubbed finish ideal for use on antiques, fine furniture, or bare wood. This product provides a durable water and alcohol resistant oil finish. Tung Oil is formulated to be absorbed into wood, creating a finish that will not crack, chip, or peel.

### Surface Preparation

All surfaces must be clean, dry, and free from dirt, wax, grease, glue and other contaminants or penetration and adhesion will be affected.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

### Application

1. Apply Old Masters Tung Oil with a lint-free cloth or by hand.
2. When the entire area has been coated, wipe off excess oil with a soft, lint-free cloth.
3. If a second coat is desired, allow the first coat to dry (about 12 hours), then rub down with 0000 steel wool.
4. Repeat steps 1 and 2. Do not apply more coats than the wood can absorb.

### Thinning

Do not thin.

### Clean Up

For cleanup, we recommend using a cleaning solvent that is compliant in your air quality management district. Check with your local government agencies to ensure proper compliance.

**DANGER:** Rags, steel wool, sanding residue, and other wastes used or soaked with this product may spontaneously catch fire if improperly discarded. No ignition source is required for these wastes to start on fire by themselves. Immediately place rags, steel wool, sanding residue, and other wastes used or soaked with this product in a sealed, water-filled metal container. Dispose of in accordance with local fire regulations.

### Limited Warranty

Since Old Masters does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters liability will under no circumstances exceed the replacement of the product.

### Product Codes

90008	Pint
90004	Quart
90001	Gallon

### Technical Data

#### Product Information

Solids by Volume	99%
Solids by Weight	99%
Weight per Gallon	7.9 lbs
Vehicle	Oil
Viscosity at 77°F	53 secs. #2 Zahn
Flash Point	400°F Tag Closed Cup
Recommended Thinner	Mineral Spirits
VOCs	<25 g/L

#### Coverage

Theoretical Coverage @ Mil DFT	300 to 400 sq ft/gal
Coverage @ Recommended DFT	N/A
Recommended DFT Per Coat	N/A

#### Dry Time

At 70°F and 50% Relative Humidity	Approximately 8 to 12 hours
-----------------------------------	-----------------------------