

## TUNG OIL VARNISH

### Description

Old Masters Tung Oil Varnish creates a beautiful, hand-rubbed finish on previously stained or bare wood. This product is a superior quality finish made from a blend of Tung oil and fine varnishes. It dries to a durable, non-oily finish which is water and alcohol resistant. It penetrates the wood surface to protect fine furniture, enhancing the natural beauty and richness of the woodgrain.

### Surface Preparation

All surfaces must be clean, dry and free from dirt, wax, grease, glue and other contaminants.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

### Application

1. Apply Old Masters Tung Oil Varnish with a lint-free cloth, rubbing in the direction of the woodgrain. For brushing applications, brush in the direction of the woodgrain.
2. Wipe off excess with a clean, lint-free cloth.
3. Allow the surface to dry 4 to 6 hours.
4. Buff lightly with fine steel wool and remove dust prior to recoating.
5. Reapply. Subsequent coats of Tung Oil Varnish will increase the depth and luster of the finish.

### Thinning

Do not thin. Use as packaged.

### Clean Up

Using a cleaning solvent, such as paint thinner or mineral spirits, is recommended for cleanup. The use of paint thinners or mineral spirits may violate VOC compliancy in your area. Check with your local government agencies to ensure proper compliancy.

**DANGER:** Rags, steel wool, sanding residue, and other wastes used or soaked with this product may spontaneously catch fire if improperly discarded. No ignition source is required for these wastes to start on fire by themselves. Immediately place rags, steel wool, sanding residue, and other wastes used or soaked with this product in a sealed, water-filled metal container. Dispose of in accordance with local fire regulations.

### Limited Warranty

Since Old Masters does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters liability will under no circumstances exceed the replacement of the product.

### Product Codes

Available Sizes: Pint (08), Quart (04), and Gallon (01)

50508	Pint
50504	Quart
50501	Gallon

### Technical Data

#### Gloss Levels at 60°

Non-porous Surface	90
--------------------	----

#### Product Information

Solids by Volume	42% to 43%
Solids by Weight	47% to 48%
Weight per Gallon	7.1 to 7.2 lbs
Vehicle	Oil/Varnish
Viscosity at 77°F	25 to 30 secs. #2 Ford Cup
Flash Point	102°F
VOCs	450 g/L

#### Coverage

Theoretical Coverage @ Mil DFT	678 sq ft/gal
Coverage @ Recommended DFT	N/A
Recommended DFT Per Coat	.5 to 1.0 mil

#### Dry Time

At 70°F and 50% Relative Humidity	Approximately 4 to 6 hours
-----------------------------------	----------------------------